

# Genuine Toro® Dingo® Attachments

## **Superior design for long-lasting, dependable performance and the perfect fit.**

Genuine Toro® Dingo® attachments are your best assurance for attaining a long life and peak performance from your loader. Toro offers a multitude of attachments that are designed specifically for, and fit the front of, the Dingo machine. The attachments are easy to operate, delivering clear sight lines, excellent operator mobility, plus easy on and off — typically in seconds.

Protect your investment by using only genuine Toro attachments that include ...

- **Optimized performance** that comes from attachments Toro engineers specifically designed for the Toro Dingo.
- **Shielded seals** on hydraulic attachments, providing two protective components to the vital hydraulic mechanism.
- **Heavy-duty, high-performance hydraulic motors** with flow and pressure ratings designed for optimal operation and life of the equipment.
- **Heavy-duty bearings** working in the heart of each design for longer life.
- **High-abrasion-resistant materials** on all ground-engaging parts, proven to sustain years of heavy use.

## **Change attachments in seconds with no lifting. Easy as 1-2-3.**



1) Mount to the attachment plate on the unit.



2) Twist pins to locked position.



3) For powered attachment, connect hydraulic lines to dripless flush-face quick couplers on loader arms.

“We were using a dedicated trencher before on drainage projects. But we decided to replace it with a more multipurpose tool that we could use year-round. A compact utility loader fits a niche need on our course, and we can do a million things with it.”

– Pete Wendt, superintendent of the Kinloch Golf Club in Manakin Sabot, Va.

### High-Speed Trencher

- Ideal for fast, efficient trenching in soft to medium soil conditions
- Heavy-duty nose roller bearing and reversible abrasion-resistant boom
- 24", 36" and 48" booms available
- Auger speed: 187 rpm at 11gpm
- Torque: 442 ft/lbs at 3000 psi
- Weight: 390 lbs.

### High-Torque Trencher

- Guarantees performance in any soil condition from rock to clay
- Heavy-duty nose roller bearing and reversible abrasion-resistant boom
- 24", 36" and 48" booms available
- Auger speed: 120 rpm at 11gpm
- Torque: 675 ft/lbs at 3000 psi
- Weight: 390 lbs.



Shown with 12" chain spacer kit.  
See parts catalog for details.



### Leveler

- Grade, finish, and spread topsoil and other landscape materials. Back fill trenches.
- Carry job site materials such as plants, fertilizer, irrigation supplies, and more.
- Length: 36", Width: 49", Height: 16"; Weight: 170 lbs.



### Stump Grinder

- Index position of blade adjusts up to 30°, allowing easy removal of roots.
- Cuts up to 36" above and 16.5" below grade.
- Wheel diameter: 17"; Teeth count: 12 carbide tipped; Wheel speed: 2000 rpm; Tooth tip speed: 145 ft/sec.
- Width: 44" with debris shield, Length: 20", Height: 31"; Weight: 265 lbs.



### Tree Forks

- Opens wide to handle large trees and shrubs.
- Angle design allows for gentle handling of materials.
- Overall width: 24.5", Overall length: 45", Overall height: 12.5", Opening at tip: 25"; Weight: 169 lbs.

### Trench Filler

- Fill trenches in a single pass, saving time and money
- Two sets of opposing augers direct spoils into the hole
- Standard float mechanism allows for up to 5" of ground following floatation
- Skids evenly disperses weight and slide easily over turf, minimizing damage
- Overall width: 62"
- Working width: 48"
- Auger diameter: 14"
- Float distance: 6"
- Weight: 410 lbs.



### TX Platform

- Bolts easily onto any Toro Dingo TX model excluding TX 413
- Special pivot point lets the platform flow with the terrain, increasing operator comfort and safety
- Helps minimize operator fatigue when traveling long distances
- Platform can be flipped out of the way at any time
- Width: 29"
- Operating height (from ground): 5"
- Weight: 94 lbs.



### Buckets

- Standard bucket: Holds 4.3 cubic feet; Width: 42"
- Narrow bucket: Holds 3.5 cubic feet; Width: 34.5"
- Light materials bucket: Holds 6.9 cubic feet; Width: 48"
- Optional tooth bars available. See parts catalog for details



### Universal Swivel Auger Power Head

- Ensures "plumb" holes on uneven terrain
- Recommended for augers up to 18"
- Perfect for installing fences
- Bit speed: 80 rpm @ 11 gpm
- Torque: 1060 ft/lbs at 3000 psi @ 11 gpm
- Dig up to 7' holes
- Bit length 42"; 1' and 2' extensions available
- Optional cement bowl



### Bore Drive Head and Rod & Reamer Kit

- Easily bore under driveways and sidewalks to simplify irrigation and cable installations. Working depth: 19.38".
- Features universal joint keeping rods in horizontal digging position, regardless of head position.
- Standard Rod & Reamer Kit: Boring Bit: 1.75"; Reamer: 2.5"; Drill rods (4): .875" diameter, by 5'. Optional bits from 1.25"-2.5"; Optional reamers up to 4.5".

### High-Torque Auger Power Head

- Designed specifically to power up to 30" diameter auger in tough soil conditions
- Excellent for digging holes for trees, footings or irrigation valve boxes 1514 ft/lbs. of torque @ 3000 psi
- Heavy-duty motor, casting and bearings
- Auger bits from 6" to 30"
- Bit length: 42"
- Bit speed: 54 rpm @ 11 gpm
- 1' and 2' extensions available
- Optional cement bowl



### Soil Cultivator

- Prepares seed bed in one pass, tilling soil up to 5.5" deep
- Adjustable grading bar and comb teeth leave perfect germination environment
- Bury stones, soil clods, debris and grass
- Totally enclosed oil bath drive system increases power and torque to the tiller shaft and tines
- Working width: 36"
- Overall width: 51", Overall height: 21", Overall Length: 51"; Weight: 550 lbs.



### Hydraulic Breaker

- Horizontal and vertical positions for demolishing driveways, sidewalks, steps, or walls
- Powerful; delivers 180 ft/lbs of force and up to 1250 blows per minute
- Tool length: 10", Tool diameter: 1.8", Overall width: 24.5", Overall length: 50"; Weight: 262 lbs.
- Optional bits available: 2" chisel; 6.5" asphalt; 8" tamper; moil bit. See parts catalog for details



### Cement Bowl

- Flighting mixes and holds cement in bowl
- Mix, haul, and pour up to 200 lbs
- Auger power head required (sold separately)
- Diameter: 25.15", Length: 18.25"; Weight: 75 lbs.



### Utility Blade

- Designed for versatility, this 48" blade angles 30° both right and left with the flip of a lever
- The blade can be removed and rotated 180° to increase blade life
- Overall width: 48", Overall height: 20.75"; Overall weight: 140 lbs.

### Tiller

- Heavy-duty, high-torque design
- Hardened steel tines for any soil condition, including clay or hardpan
- Till more than six inches deep and 40" wide on one pass
- Reversible tine direction frees jams quickly
- Tine speed: 226 rpm @ 11 gpm
- Overall width: 44"
- Overall length: 20"
- Height: 26"
- Weight: 363 lbs.



### Backhoe

- Versatile — dig foundations, plant trees, trench and much more
- Folds to 34.5" wide for access to tight spaces and ease of transport
- 180° bucket and swing arm rotation, 82" digging depth, and standard 13" bucket
- Transport height: 71"
- Weight: 762 lbs.
- Stabilizer spread: 78"
- Bucket digging force: 2450 lbs.
- Crowd arm digging force: 1250 lbs.



### Grapple Rake

- Exceptional power for clamping and holding
- Ideal for picking up and removing trees, bushes, roots and rocks — as well as demolition and construction debris
- Tines constructed of 3/8" AR400 steel\*
- Overall width: 34.5"; Weight: 270 lbs.; Clamping force: 3000 lbs.



### Adjustable Forks

- Easily adjust forks to desired width
- Carry fence posts, rocks, pallets, plants, fertilizer, irrigation supplies and more
- Forks constructed of high-strength T1 steel
- Lift capacity: 335 lbs.; Maximum lift height: 61"; Width: 31.3"; Weight: 167 lbs.



### Snowthrower

- Two-stage design with the power to handle the toughest snow conditions
- Replaceable scraper
- Adjustable skids
- Overall Width: 48"; Clearing width 44"
- Auger diameter: 16"; Auger speed: 161 rpm @ 11 gpm; Weight: 312 lbs.

\*Nearly twice as hard, 50% better wear than T1 steel

### Power Box Rake

- Perfect tool for seed bed and sod bed preparation
- Easily adjust depth to fill, plane and pulverize soil
- Carbide-teeth rotary drum pulverizes rough soil, cuts high spots and fills low spots in one pass
- Roller drum removes rocks and debris, leaving dimpled surface for moisture retention
- Reversible end plates for forward or reverse operation
- Adjustable yoke allows 20° offset
- Overall width: 67"
- Working width: 48"
- Overall height: 40"
- Overall length: 26"
- Weight: 510 lbs.



### Vibratory Plow

- Optimizes pipe-pulling performance while minimizing turf damage to reduce time and labor spent on irrigation or cable installations
- Pulls pipe up to 18" deep
- Elliptical vibrating motion moves pipe through difficult soil conditions
- Head flexes side-to-side for tight turning
- Pipe size: up to 1.5" flexible polyethylene with standard bullet; 2" PVC or 80lb. polypipe with taperlock puller
- Swing angle: +/- 30°
- Plow cycle: 1390 vpm
- Max. plow speed: 88 ft/min depending on soil conditions
- Overall length: 34", Overall width: 28.2", Overall height w/out blade: 27"; Overall weight: 457 lbs.



### Multi-Purpose Tool

- 3 tools in 1: ripper, towbar, boom
- Ripper: 3 thick steel tines — great for digging & breaking up soil
- Towbar: Accepts ball with 1" diameter threads (ball not included)
- Boom & chain length 45"; ideal for planting and hauling trees and shrubs