

Height with Cab

Wheel	26x12.00-12	400/50-15
size	or 320/60-12	
Cab L	82.3 in	84.3 in
Cab LX	81.8 in	83.9 in
Cab DLX	82.9 in	85.4 in
Cab DLX with Air conditioning on the roof	88.2 in	90.7 in

Width 755i

Wheel size	Profile	Machine width
26 x 12.0 - 12	TR/Grass	50.8 in
320/60 - 15	TR	50.8 in
27 x 8.5 - 15	TR	40.6 in

Width 760i

Wheel size	Profile	Machine width
400/50 - 15	TR/Grass	57.1 in
320/55 - 15	TR/Grass	53.5 in
27 x 8.5 - 15	TR	42.5 in
		46.6 in

Model	AVANT 755i	AVANT 760i
Length	120.9 in	120.9 in
Width (standard tires)	51 in	57.1 in
Height	82.3 in	84.3 in
Weight, starting from	4420 lb	4640 lb
Standard tires	26/12.00-12 Grass, 320/60-12 Tractor	400/50-15 TR or grass
Transmission	Hydrostatic	Hydrostatic
Pulling force	2990 lbf	3600 lbf
Drive speed	10.5 mph	18.6 mph
Auxiliary hydraulics	21.1 gal/min 3260 PSI	21.1 gal/min 3260 PSI
Turning radius (inside/outside)*	49.2 / 105.3 in	49.2 / 105.3 in
Lifting height	122.0 in	122.0 in
Tipping load**	3810 lb	3810 lb
Max. breakout force at 20 in	3750 lbf	3750 lbf
Engine make and type	Kohler KDI 1903 TCR	Kohler KDI 1903 TCR
Engine output	57 hp	57 hp
Fuel	diesel	diesel
Product no:	A21728	A21730

^{*} With standard wheels

^{**} Load is measured at 15.8 in from the attachment coupling plate, unit with rear sideweights.

Height with Cab	26x12.00-12 and 320/60-12	320/55-15	400/50-15 and 31x15.5-15
Cab LX	81.8 in	83.1 in	83.9 in
Cab DLX	82.9 in	84.2 in	85.4 in
Cab DLX with Air conditioning on the roof	88.2 in	89.6 in	90.7 in