

Cat[®] Snow Blowers

SKID STEER LOADERS
MULTI TERRAIN LOADERS
COMPACT TRACK LOADERS
COMPACT WHEEL LOADERS

Cat[®] Snow Blowers are designed for removing snow from streets, parking lots, driveways and sidewalks, making them ideal for winter cleanup and maintenance applications.

Features:

Two-stage design uses auger and impeller

- Two-stage design uses auger and impeller to move a greater capacity of snow quickly and efficiently. Also, a reversible auger and impeller allows operator to expel obstructions without exiting the machine.

Exclusive in-line impeller

- Exclusive in-line impeller draws in only as much snow as it can throw, providing the appropriate balance of speed and torque to maximize capacity and throwing distance.

Adjustable impeller relief valve

- Fine tune performance for wet/heavy or light snow.
- Maintains throwing distance during auger stall conditions.

Hydraulically controlled chute, auger, impeller and deflector

- Chute, auger, impeller and deflector provide easy adjustment, long life and less maintenance.

Machine joysticks control chute and deflector

- There are no additional wires or hardware to connect. Complete control with plug-n-play simplicity.

180° chute rotation

- Rotation permits snow discharge to front or sides of machine preventing snow blow back on operator.

Rugged snow releasing cab access steps

- Wide steps with grating and large profile serrations provide better boot traction.

Non-binding rotating discharge chute

- Non-binding rotating discharge chute utilizes non-metallic liner to prevent plugging and freeze ups.

Smooth chute design

- Design eliminates ledges to prevent bridging and plugging.
- Deep chute produces smoother, more controllable stream of snow.

Nickel-plated corrosion-resistant chute chain

- Chute chain prevents chain rust that could negatively affect chain life and performance.

Bolt-on replaceable reversible cutting edge and large skid shoes

- Bolt-on replaceable reversible cutting edge and large skid shoes extends snow blower work tool life.

Diverter manifold cover and wire sleeving

- Diverter manifold cover and wire sleeving protect components from damage.

Compatibility

Model	Machines
SR117	226B3, 247B3
SR118#	236D, 246D, 257D, 259D, 262D, 272D, 272D XHP, 277D, 279D, 287D, 289D, 299D, 299D XHP, 906H2, 907H2, 908H2
SR121#	236D, 246D, 257D, 259D, 262D, 272D, 272D XHP, 277D, 279D, 287D, 289D, 299D, 299D XHP, 906H2, 907H2, 908H2
SR318*#	226B3, 246D, 257D, 259D, 262D, 272D, 272D XHP, 277D, 279D, 287D, 289D, 299D, 299D XHP, 906H2, 907H2, 908H2
SR321*#	226B3, 246D, 257D, 259D, 262D, 272D, 272D XHP, 277D, 279D, 287D, 289D, 299D, 299D XHP, 906H2, 907H2, 908H2


* Requires high flow and high flow XPS option on machine. Operates in high flow XPS on XHP machine.

Requires a conversion kit for D Series and H Series 2 machines.



Cat Snow Blowers

Specifications



			SR117	SR118	SR121	SR318	SR321
A Intake width	mm (in)		1702 (67)	1854 (73)	2159 (85)	1854 (73)	2159 (85)
B Overall width	mm (in)		1765 (69.5)	1918 (75.5)	2223 (87.5)	1918 (75.5)	2223 (87.5)
C Cutting height	mm (in)		610 (24)	826 (33)	883 (35)	826 (33)	883 (35)
D Overall height	mm (in)		1797 (71)	1797 (71)	1797 (71)	1957 (77)	1957 (77)
E Overall length	mm (in)		1148 (45.2)	1209 (47.6)	1440 (56.7)	1209 (47.6)	1440 (56.7)
Weight	kg (lb)		419 (924)	474 (1,045)	591 (1,303)	475 (1,047)	592 (1,305)
Maximum throw	m (ft)		9.1 (30)	12.2 (40)	12.2 (40)	13.7 (45)	13.7 (45)
Auger diameter	mm (in)		305 (12)	406 (16)	457 (18)	406 (16)	457 (18)
Impeller/fan diameter	mm (in)		517 (20)	517 (20)	679 (27)	517 (20)	679 (27)
Impeller/fan width	mm (in)		229 (9)	279 (11)	279 (11)	279 (11)	279 (11)
Chute rotation			180°	180°	180°	180°	180°
Required hydraulic flow	L/min (gpm)		53-75 (14-20)	68-83 (18-22)	68-87 (18-23)	98-130 (26-34)	98-130 (26-34)
Hydraulic pressure	bar (psi)		230 (3,340)	230 (3,340)	230 (3,340)	280 (4,065)	280 (4,065)

Theoretical values calculated at 100% efficiency.

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2013 Caterpillar Inc.
All Rights Reserved
Printed in U.S.A.

AEHQ5845-05 (08-13)
Replaces AEHQ5845-04

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

