

Specification	T-10D	T-12D
Capacity (pounds)	10,000	12,000
GVWR (pounds)	12,900	14,900
GAWR (pounds)	12,000	12,000
Avg. Weight (pounds)	2,900	2,900
Load Width (in)	82"	82"
Deck Height (in) unloaded	22"	22"
Std. Hitch Size (in)	2.5"	2.5"
Tongue/Gooseneck Length (ft)	5'-0"	5'-0"
Safety Chain	3/8 Gr. 43	3/8 Gr. 43
Parking Jack	12K	12K
Bolted-on Parking Jack	Y	Y
Main Beam	6" I-Beam	6" I-Beam
Deck Type	Drop-Deck	Drop-Deck
Deck Safety Lip	Y	Y
Deck Material	White Oak	White Oak
Added Stationary Deck	N/A	N/A
Ramp Size (ft x in)	5'-0"x18"	5'-0"x18"
Load Angle (degrees)	17	17
Dump Angle	N/A	N/A
Beavertail	O	O
Ramp Hold-Up	Auto-Latch	Auto-Latch
Ramp Spring Assist (off deck)	N/A	N/A
Ramp Spring Assist (off ground)	Std.	Std.
Tie Downs	D-rings	D-rings
No. of Tie Downs	8	8
Axle Capacity	7K	7K
No. of Axles	2	2
Axle Spread (in)	34"	34"
Hubs	EZ-Lube	EZ-Lube
Brake Size	12" x 2"	12" x 2"
Electric Brakes	Std.	Std.
Air Brakes	N/A	N/A
Wheels (size)	16"	16"
Wheel Bolt Pattern	8-bolt	8-bolt
Tires	235/85Rx16	235/85Rx16
Tire Load Rating	E	E
Lights	LED	LED
Full Warranty	1 Year	1 Year
Frame Warranty	10 Year	10 Year